

**Serie | 2, wall-mounted cooker hood,  
60 cm, Stainless steel  
DWB64BC51B**



**Box-design hood: performance and  
matching kitchen design bundled in one  
hood.**

- **Silent:** maximal extractor performance with little noise
- **Grease filtration level:** filters out over 85% of the grease from kitchen air
- **LED-illumination:** The energy-saving lighting provides white and good lighting for the hob area.
- With exhaust, the air is cleaned by a grease filter and then ducted to the outside which ensures optimal kitchen air quality.

**Technical Data**

Typology :	Chimney
Approval certificates :	CE, G-Mark, VDE
Length electrical supply cord (cm) :	130
Height of the chimney (mm) :	583-912/583-1022
Height of product, without chimney (mm) :	53
Net weight (kg) :	10.982
Type of control :	mechanical
Number of speed settings :	3
Maximum output air extraction (m <sup>3</sup> /h) :	365
Maximum output recirculating air (m <sup>3</sup> /h) :	196
Number of lights :	2
Noise level (dB) :	63
Diameter of air outlet (mm) :	120 / 150
Grease filter material :	Washable stainless steel
Odour filter :	No
Operating Mode :	Convertible
Optional accessories :	DHZ1225, DHZ1235, DHZ6550, DHZ6551, DWZ0DX0A0, DWZ0DX0U0, DWZ0XX0J0, DWZ1DX1I6, DWZ1FX5C6, DZZ1XX1B6, DWZ1FX5D1, DZZ0XX0P0
Type of lamps used :	LED
Grease filter type :	Kassette
Connection Rating (W) :	100
Current (A) :	10
Voltage (V) :	220-240
Frequency (Hz) :	50; 60
Plug type :	GB plug
Installation typology :	Wall-mounted
Material body :	Stainless steel
Approval certificates :	CE, G-Mark, VDE
Plug type :	GB plug
Dimensions of the product, with chimney (if exists) (in) :	/ x x
Dimensions of the packed product (in) :	19.29 x 25.59 x 28.74
Net weight (lbs) :	24.000
Gross weight (lbs) :	35.000
Motor location :	Integrated motor in hood chimney
No-return airflow flap :	No
Length electrical supply cord (cm) :	130
Dimensions of the product, with chimney (if exists) (mm) :	635-1075 MM x 600.0 x 500.0
Dimensions of the packed product (HxWxD) (mm) :	490 x 650 x 730
Net weight (kg) :	10.982
Gross weight (kg) :	15.9



**Serie | 2, wall-mounted cooker hood, 60 cm,  
Stainless steel  
DWB64BC51B**

**Box-design hood: performance and matching  
kitchen design bundled in one hood.**

**Measures:**

- 600 mm width
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Dimensions exhaust air (HxWxD): 635-965 x 600 x 500 mm
- Dimensions recirculating (HxWxD): 635-1075 x 600 x 500 mm
- Dimensions recirculating with CleanAir module (HxWxD): 703 x 600 x 500 mm - mounting with outer chimney 833-1163 x 600 x 500 mm - mounting with telescopic chimney
- Electrical cable length 1.3 m

**Variant:**

**Design:**

- 60 cm Chimney hood
- Wall mounted hood
- Appliance colour: stainless steel

**Technical information:**

- Power rating: 100 W

**Environment and safety:**

- Energy Efficiency Class: D\*
- Average Energy Consumption: 53.1 kWh/year\*
- Blower Efficiency Class: E\*
- Lighting Efficiency Class: A\*
- Grease Filtering Efficiency Class: B\*

**Comfort:**

- Suitable for ducted or re-circulated extraction
- For recirculated extraction or CleanAir recirculation kit (accessory) needed
- push buttons for extractor speeds and light
- 3 speeds via push buttons
- Twin channel high performance fan motor
- Maximum extraction rate exhaust air 365 m<sup>3</sup>/h according to EN 61591
- Extraction rate in recirculation mode: Max. normal use: 196 m<sup>3</sup>/h
- Noise level in recirculation mode: Max. normal use: 66 dB(A) re 1 pW (53 dB(A) re 20 µPa sound pressure)
- Metal grease filter, dishwasher safe
- 2 x 1,5W LED
- Light Intensity: 99 lux
- Colour Temperature: 3500 K
- Noise level according to EN 60704-3 und EN 60704-2-13 at max. normal use exhaust air: 63 dB(A) re 1 pW (50 dB(A) re 20 µPa sound pressure)
- Noise min./max. Normal Level: 48/63 dB\*

**Serie | 2, wall-mounted cooker hood, 60 cm,  
Stainless steel  
DWB64BC51B**

